# MORE ABOUT ROOF FLASHING 4 u" 12 u, 14 1.

# **WHY ROOF EDGES FAIL**


Tile roofing, especially concrete "S" shaped tile, is a popular roofing choice for residential construction and is used extensively throughout the Southwestern states. It offers a combination of attractiveness, durability, fire resistance, and generally low maintenance.

Unfortunately, construction of the open roof edges (eaves and rakes) – both extended and clipped – is often incomplete, resulting in damaging leaks to the supporting framing. In the case of increasingly popular "zero-overhang" designs with clipped eaves or rakes, leakage may extend to interior finishes and contents.

### **EAVES**

The first row of tile is typically boosted along eave edges, often done with a standard, self-draining, metal booster strip. Other designs accomplish this by a raised wood fascia or additional wood trim, which requires an "antiponding" device (such as an extended metal edge or other filler) to support the tile underlayment sheet behind the trim (see below). Unfortunately, this requirement is often overlooked.

### PROBLEMATIC CONSTRUCTION




**EAVE** 

**Building Analysts** is a full-service architectural firm, specializing in construction analysis and litigation support, quality assurance, and peer review services. If you need our expert advice or recommendations, please contact us at **analysts@buildinganalysts.com**, or visit our web site for further information.

### **EAVES & RAKES WITHOUT OVERHANG**

Where clipped roof eaves and rakes occur, a sheet metal drip edge is advised by roofing trade associations and tile manufacturers, which, when properly installed and lapped with the underlayment, greatly reduces the likelihood of leakage to the building framing and interior.

### PROBLEMATIC CONSTRUCTION




**RAKE WITHOUT OVERHANG** 

## **RAKES AT OVERHANGS**

When extended rake edges are installed without edge metal, it is advised to fold down the ends of the tile underlayment approximately 2" to cover the edge of the wood sheathing under the rake tile and avoid damage of the framing.

### PROBLEMATIC CONSTRUCTION



**RAKE WITH OVERHANG** 

Building Analysts' newsletter is intended to provide general information for those involved in construction litigation. The topics contained in this publication are abbreviated and applicability to a particular situation may vary according to circumstances. Since design and construction technologies change over time, the information contained herein may become outdated. Building Analysts recommends you contact the appropriate design professional for specific information regarding individual projects.

WINTER 2004 Next Issue: SPRING 2004